



TYPE IV

NOTES

AGGREGATE BASE SHALL BE ELIMINATED WHEN CONTROLLED DENSITY FILL IS USED FOR COMPACTED BACKFILL.

ALL MATERIALS AND CONSTRUCTION SHALL CONFORM TO THE CURRENT CITY OF COLUMBUS "CONSTRUCTION AND MATERIAL SPECIFICATIONS".

BACKFILL OF ALL TRENCHES SHALL BE IN ACCORDANCE WITH STANDARD DRAWINGS C-GC-66, C-GC-67 AND C-GC-68.

TEMPORARY REPAVEMENT SHALL BE PLACED ON THE SAME DAY THE ORIGINAL PAVEMENT IS CUT.

ALTERNATE BACKFILL - CONTROLLED DENSITY FILL WITH A MINIMUM DENSITY OF 125 LBS./CU. FT. CONSISTING OF A CEMENTITIOUS MATERIAL.

ITEM NUMBERS SHOWN REFER TO THE CURRENT CITY OF COLUMBUS "CONSTRUCTION AND MATERIAL SPECIFICATIONS".

APPROVED
EVANS, MECHWART, HAMBLETON & TILTON, INC.

By

[Signature]
[Signature]
CITY ADMINISTRATOR

PAVEMENT
REPLACEMENT
(TEMPORARY)

CITY OF
GROVE CITY, OHIO

STANDARD
CONSTRUCTION DRAWING

REV.

DATE
3-31-88

DWG. Nº
C-GC-69